

Undercounter Beer Cooler, Water Cooling System

AS - 80. 2011



- The **AS-80 .2011** Beer Cooling System is designed for professional beverage cooling in restaurants, bars and the catering industry.
- This machine has a pump with displacement of 6m, thanks to which the cooler may be situated in the cellar, keeping the beverage chilled all the way to the tap.
- The **AS-80 .2011** has a continuous cooling capacity of 50-80l/h.
- The modern compressor cooling unit uses the power input for direct transfer to chilling, which guarantees minimum energy usage.
- **LINDR cooling technology is 45% more efficient** than its power input.
- The cooling coils are made from stainless steel.
- The materials used meet the highest requirements for hygiene standards and guarantee a long working life of this cooler.
- Two grab handles on the side of the machine enables the machine to be carried and moved with ease.
- The cooler also includes an adjustable temperature control with 7 different settings.

- The overflow on the side of the cooler is for regulation of the capacity of the water tank.
- Simple to use push-in fittings on top of the cooler ensure easy connection to the beverage supply.
- AS coolers maintain a leading position among professional coolers on the market due to their modern technology and performance.

Output (l/hod) T_0 0 °C / T_k 50 °C	80
Displacement of water pump (m)	6
Number of cooling coils (pcs)	2- 4
Dimensions (w x h x d) in mm	530 x 455 x 330
Weight (kg)	29.0

