

# Undercounter Beer Cooler, Water Cooling System

## AS - 110 .2011



- The **AS-110 .2011** Beer Cooling System is designed for professional beverage cooling in restaurants, bars and the catering industry.
- **This machine has a pump with displacement of 8m**, thanks to which the cooler may be situated in the cellar keeping the beverage chilled all the way to the tap.
- The **AS-110 .2011** has a continuous cooling capacity of 75-110l/h.
- The modern compressor cooling unit uses the power input for direct transfer to chilling, which guarantees minimum energy usage.
- **LINDR cooling technology is 45% more efficient** than its power input.
- The cooling coils are made from stainless steel.
- The materials used meet the highest requirements for hygiene standards and guarantee a long working life of this cooler.
- The cooler also includes an adjustable temperature control with **7 different settings**.

- The overflow on the side of the cooler is for regulation of the capacity of the water tank.
- Simple to use push-in fittings on top of the cooler ensure easy connection to the beverage supply.
- **Two grab handles** on the side of the machine enables the machine to be carried and moved with ease.
- AS coolers maintain a leading position among professional coolers on the market due to their modern technology and performance.

<b>Output</b> (l/hod) $T_o$ 0 °C / $T_k$ 50 °C	110
<b>Displacement of water pump</b> (m)	8
<b>Number of cooling coils</b> (pcs)	2-6
<b>Dimensions</b> (w x h x d) in mm	610 x 475 x 420
<b>Weight</b> (kg)	34.0

